



# BENJAMIN MOORE NATURA<sup>®</sup> PREMIUM INTERIOR PAINT & PRIMER FLAT K512

## Features

- Zero VOC
- Quick return to service
- 100% Acrylic
- Spatter-resistant
- Self-priming on most surfaces
- Dries quickly to a beautiful, washable, and uniform flat finish

## Recommended For

New or previously painted interior wallboard, plaster and masonry, as well as primed or previously painted wood and metal. Provides a beautiful flat finish on walls and ceilings.

## General Description

Benjamin Moore Natura<sup>®</sup> Premium Interior Paint & Primer, Flat (K512) is a premium quality, zero VOC paint that provides a durable, washable and fade-resistant finish. Benjamin Moore Natura<sup>®</sup> Premium Interior Paint & Primer, Flat (K512) is ideally suited for residential applications and is Certified asthma & allergy friendly<sup>™</sup>.

## Limitations

- Do not paint when air and surface temperatures are below 10 °C (50 °F)

## Product Information

### Colours — Standard:

White (01)

### — Tint Bases:

Benjamin Moore<sup>®</sup> Gennex<sup>®</sup> Bases 1X, 2X, 3X, & 4X

### — Special Colours:

Contact your Benjamin Moore representative.

### Certifications & Qualifications:

#### VOC compliant in all regulated areas

Zero VOC

Zero Emissions

Class A (0-25) over non-combustible surfaces when tested in accordance with ASTM E-84

Master Painters Institute MPI # 53, 53 X-Green<sup>™</sup>, 143, 143 X-Green<sup>™</sup>



This product meets Green Seal<sup>™</sup> Standard GS-11 based on effective performance, minimized/recycled packaging, and protective limits on VOCs and human toxicity. [GreenSeal.org](http://GreenSeal.org)



Benjamin Moore's Green Promise<sup>®</sup> designation is our company's assurance that this product meets – and often exceeds – rigorous environmental and performance criteria regarding VOCs, emissions, application, washability, scrubability and packaging, while also delivering the premium levels of performance you expect from Benjamin Moore.

Qualifies for LEED <sup>®</sup> v4 Credit	CDPH v1 Emission Certified	Qualifies for CHPS low emitting credit (Collaborative for High Performance Schools)	VOC (in any colour)
YES	YES	YES	0 g/L

### CUSTOMER SERVICE INFORMATION CENTRE:

1-800-361-5898, [info@benjaminmoore.ca](mailto:info@benjaminmoore.ca), [www.benjaminmoore.ca](http://www.benjaminmoore.ca)

### Technical Data<sup>◇</sup>

Vehicle Type	100% Acrylic Latex
Pigment Type	Titanium Dioxide
Volume Solids	45.5%
Coverage per 3.79 L at Recommended Film Thickness	34.8 – 39.5 sq. m. (375 – 425 sq. ft.)
Recommended Film Thickness	– Wet 4.0 mils – Dry 1.8 mils

Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure colour uniformity and minimize the disposal of excess paint

Dry Time @ 25 °C (77 °F) @ 50% RH	– To Touch 30 Minutes – To Recoat 1 – 2 Hours
-----------------------------------	--

Painted surfaces can be washed after two weeks. High humidity and cool temperatures will result in longer dry, recoat and service times

Dries By	Evaporation, Coalescence
Viscosity	108 ± 2 KU
Flash Point	None
Gloss / Sheen	Flat (1.5-3.5 @ 85°)
Surface Temperature at Application	– Min. 10 °C (50 °F) – Max 32.2 °C (90 °F)
Thin With	See Chart
Clean Up Thinner	Clean Water
Weight Per 3.79 L	5.05 kg (11.1 lbs)
Storage Temperature	– Min. 4.4 °C (40 °F) – Max 32.2 °C (90 °F)

### Volatil Organic Compounds (VOC)

0 g/L

**Zero VOC post tint (any base and any colour)**

<sup>◇</sup>Reported VOC values are for all bases/colours.

## Benjamin Moore Natura® Premium Interior Paint & Primer Flat K512

### Surface Preparation

Surfaces to be painted must be clean, dry, and free of dirt, dust, grease, oil, soap, wax, scaling paint, water soluble materials and mildew. Remove any peeling or scaling paint and sand these areas to feather edges smooth with adjacent surfaces. Glossy areas should be dulled. Drywall surfaces must be free of sanding dust.

New plaster or masonry surfaces must be allowed to cure (30 days) before applying base coat. Cured plaster should be hard, have a slight sheen and maximum pH of 10; soft, porous or powdery plaster indicates improper cure. Never sand a plaster surface; knife off any protrusions and prime plaster before and after applying patching compound. Poured or pre-cast concrete with a very smooth surface should be etched or abraded to promote adhesion, after removing all form release agents and curing compounds. Remove any powder or loose particles before priming.

**Difficult Substrates:** Benjamin Moore offers a variety of specialty primers for use over difficult substrates such as plaster, bleeding woods, grease stains, crayon markings, hard glossy surfaces, galvanized metal or other substrates where paint adhesion or stain suppression is a particular problem. Your Benjamin Moore retailer can recommend the right problem-solving primer for your special needs.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada @ <https://www.canada.ca/en/health-canada/services/environmental-workplace-health/environmental-contaminants/lead/lead-information-package-some-commonly-asked-questions-about-lead-human-health.html>

### Primer/Finish Systems

Benjamin Moore Natura® Premium Interior Paint & Primer, Flat is self priming on most surfaces. Benjamin Moore Natura® will act as its own primer, providing the optimal foundation for the subsequent finish coat. On bare substrates two coats are required; previously painted surfaces can be finished with 1 or 2 coats. While the high quality of our products sometimes makes one-coat coverage achievable, Benjamin Moore recommends two coats of this product to achieve full colour development and to maximize paint film performance. **Special Note:** Certain custom colours require a Deep Colour Base Primer tinted to a special prescription formula to achieve the desired colour. Consult your retailer.

#### Wood, and Engineered Wood Products

**Primer:** Benjamin Moore Natura® Premium Interior Primer (K511)

#### For bleeding woods such as cedar and redwood:

**Primer:** Fresh Start® High-Hiding All Purpose Primer (K046) or Fresh Start® Multi-Purpose Oil Based Primer (F024)

**Finish:** 1 or 2 coats of Benjamin Moore Natura® Premium Interior Paint & Primer Flat (K512)

#### Drywall

**Primer/Finish:** 1 or 2 coats of Benjamin Moore Natura® Premium Interior Paint & Primer Flat (K512)

#### Plaster

**Primer/Finish:** 1 or 2 coats of Benjamin Moore Natura® Premium Interior Paint & Primer, Flat (K512)

#### Rough or Pitted Masonry

**Primer:** Ultra Spec® Masonry Interior/Exterior Hi-Build Block Filler (K571)

**Finish:** 1 or 2 coats of Benjamin Moore Natura® Premium Interior Paint & Primer Flat (K512)

#### Smooth Poured or Pre-cast Concrete

**Primer/Finish:** 1 or 2 coats of Benjamin Moore Natura® Premium Interior Paint & Primer Flat (K512)

#### Ferrous Metal (Steel and Iron)

**Primer:** Ultra Spec® HP Acrylic Metal Primer (FP04) or Super Spec HP® Alkyd Metal Primer (KP06)

**Finish:** 1 or 2 coats of Benjamin Moore Natura® Premium Interior Paint & Primer Flat (K512)

**Non-Ferrous Metal (galvanized & aluminum)** All new metal surfaces must be thoroughly cleaned with Corotech® Oil & Grease Emulsifier (V600) to remove contaminants. New shiny non-ferrous metal surfaces that will be subject to abrasion should be dulled with very fine sandpaper or a synthetic steel wool pad to promote adhesion.

**Primer:** Not required on properly prepared surfaces

**Finish:** 1 or 2 coats of Benjamin Moore Natura® Premium Interior Paint & Primer Flat (K512)

**Repaint, All Substrates:** Prime bare areas with the primer recommended for the substrate above.

### Application

**Mixing of Paint:** Stir thoroughly before and during use. Apply one or two coats.

**Paint Application:** For best results, use a premium Benjamin Moore® custom-blended nylon/polyester brush, premium Benjamin Moore® roller, or a similar product. Apply paint generously from unpainted area into wet area. This product can also be sprayed.

See Chart below.

### Thinning/Clean Up

Conditioning with Benjamin Moore® K518 Extender may be necessary under certain conditions to adjust open time or spray characteristics. The chart below is for general guidance		
	Mild conditions	Severe conditions
	Humid (RH> 50%) with no direct sunlight & with little to no wind	Dry (RH<50%), in direct sunlight, or windy conditions
<b>Brush:</b> Nylon / Polyester	No thinning necessary	Add <b>K518 Extender</b> or <b>water:</b>  Max of 236 ml (8 fl. oz.) to a 3.79 L  <b>Never add other paints or solvents.</b>
<b>Roller:</b> Premium Quality		
<b>Spray: Airless</b> Pressure: 1500 -2500 psi Tip: .013- .017		

**Clean up:** Wash painting tools in warm soapy water immediately after use. Spray equipment should be given a final rinse with mineral spirits to prevent rusting.

### Environmental Health & Safety Information

Use only in a well ventilated area. Keep container closed when not in use. In case of spillage, absorb with inert material and dispose of in accordance with local regulations. Wash thoroughly after handling.

**KEEP OUT OF REACH OF CHILDREN  
PROTECT FROM FREEZING**

**Refer to Safety Data Sheet for additional health  
and safety information.**

Benjamin Moore & Co., Ltd. 8775 Keele St., Concord, ON L4K 2N1 1-800-361-5898 [www.benjaminmoore.ca](http://www.benjaminmoore.ca) M72 K512 CE 072018  
Benjamin Moore, Benjamin Moore Natura, Fresh Start, Genex, Green Promise, Super Spec HP, Ultra Spec and the triangle "M" symbol are registered trademarks of Benjamin Moore & Co., Ltd. © 2009, 2018 Benjamin Moore & Co., Ltd. ASTHMA & ALLERGY FRIENDLY and ASTHMA & ALLERGY FRIENDLY LOGO are Certification Marks and Trademarks of ALLERGY STANDARDS LIMITED. The ASTHMA CANADA name and logo are Trademarks of Asthma Canada. Cradle to Cradle Certified™ is a certification mark licensed by the Cradle to Cradle Products Innovation Institute. This product is not endorsed by or a division of CHPS. This product is provided by Benjamin Moore, not CHPS. All other trademarks belong to their respective owners. All rights reserved