

SAFETY DATA SHEET

Revision Date: 02-May-2017

Revision Number: 1

1. PRODUCT AND COMPANY IDENTIFICATION

AURA WATERBORNE EXTERIOR LOW LUSTRE FINISH WHITE

Product Name Product Code Alternate Product Code Product Class Color Recommended use Restrictions on use

K63401 K63401 WATER THINNED PAINT White Paint No information available

Manufactured For

Benjamin Moore & Co., Limited 8775 Keele Street Concord ON L4K 2N1 Phone: 1-800-361-5898 www.benjaminmoore.com

Manufacturer

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 Phone: 855-724-6802 www.benjaminmoore.com Emergency Telephone Number(s) CANUTEC: 613-996-6666

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the Hazardous Products Regulations (HPR: SOR/2015-17)

| Skin sensitization | Category 1A |
|--------------------|-------------|
| Carcinogenicity | Category 2 |

Label elements

Warning

Hazard statements May cause an allergic skin reaction Suspected of causing cancer

K63401 - AURA WATERBORNE EXTERIOR LOW LUSTRE FINISH WHITE



Appearance liquid

Odor little or no odor

Precautionary Statements - Prevention

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Avoid breathing dust/fume/mist/vapors/spray Contaminated work clothing should not be allowed out of the workplace Wear protective gloves

Precautionary Statements - Response

If exposed or concerned get medical attention **Skin** If on skin wash with plenty of soap and water If skin irritation or rash occurs get medical attention Wash contaminated clothing before reuse

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other information

No information available

Other hazards

May cause allergic skin reaction

| Chemical Name | CAS-No | Weight % (max) | |
|--|------------|----------------|--|
| Titanium dioxide | 13463-67-7 | 10 - 30% | |
| Nepheline syenite | 37244-96-5 | 5 - 10% | |
| Barium sulfate | 7727-43-7 | 1 - 5% | |
| Kaolin, calcined | 92704-41-1 | 1 - 5% | |
| Zinc oxide | 1314-13-2 | 1 - 5% | |
| Silica, amorphous | 7631-86-9 | 1 - 5% | |
| Hexanedioic acid, dihydrazide | 1071-93-8 | 0.25 - 0.5% | |
| Decanedioic acid, | 41556-26-7 | 0.25 - 0.5% | |
| bis(1,2,2,6,6-pentamethyl-4-piperidinyl) ester | | | |
| Sodium C14-C16 olefin sulfonate | 68439-57-6 | 0.1 - 0.25% | |
| Urea, N-(3,4-dichlorophenyl)-N,N-dimethyl- | 330-54-1 | 0.1 - 0.25% | |

3. COMPOSITION INFORMATION ON COMPONENTS

4. FIRST AID MEASURES

| General Advice | No hazards which require special first aid measures. |
|---------------------------------|--|
| Eye Contact | Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. |
| Skin Contact | Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician. Wash clothing before reuse. Destroy contaminated articles such as shoes. |
| Inhalation | Move to fresh air. If symptoms persist, call a physician. |
| Ingestion | Clean mouth with water and afterwards drink plenty of water. Consult a physician if necessary. |
| Most Important Symptoms/Effects | May cause allergic skin reaction. |
| Notes To Physician | Treat symptomatically. |

5. FIRE-FIGHTING MEASURES

| Suitable Extinguishing Media | Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. |
|--|--|
| Protective Equipment And Precautions For Firefighters | As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. |
| Specific Hazards Arising From The Chemical | Closed containers may rupture if exposed to fire or extreme heat. |
| Sensitivity To Mechanical Impact | No |
| Sensitivity To Static Discharge | No |
| Flash Point Data Flash Point (°F) Flash Point (°C) Flash Point Method | Not applicable Not applicable Not applicable |
| Flammability Limits In Air | |
| Lower Explosion Limit Upper Explosion Limit | Not applicable Not applicable |
| NFPA Health: 1 Flammability: 0 li | nstability: 0 Special: Not Applicable |
| NFPA Legend 0 - Not Hazardous 1 - Slightly | |

- 2 Moderate
- 3 High
- 4 Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions

Other Information

Environmental Precautions

Methods For Clean-Up

Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.

Prevent further leakage or spillage if safe to do so.

See Section 12 for additional Ecological Information.

Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.

7. HANDLING AND STORAGE

Handling

Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment.

Keep container tightly closed. Keep out of the reach of

Storage

Incompatible Materials

No information available

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

children.

Exposure Limits

No exposure limits have been established for this product.

| Chemical Name | ACGIH | Alberta | British Columbia | Ontario | Quebec |
|---|----------------------------------|----------------------------------|----------------------------------|----------------------------------|--|
| Titanium dioxide | 10 mg/m³ - TWA | 10 mg/m³ - TWA | 10 mg/m³ - TWA 3 mg/m³ - TWA | 10 mg/m³ - TWA | 10 mg/m ³ - TWAEV |
| Nepheline syenite | N/E | N/E | N/E | 10 mg/m³ - TWA | N/E |
| Barium sulfate | 5 mg/m³ - TWA | 10 mg/m³ - TWA | 10 mg/m³ - TWA 3 mg/m³ - TWA | 10 mg/m³ - TWA | 10 mg/m ³ - TWAEV 5 mg/m ³ - TWAEV |
| Zinc oxide | 2 mg/m³ - TWA 10 mg/m³ - STEL | 10 mg/m ³ - TWAEV 5 mg/m ³ - TWAEV 10 mg/m ³ - STEV |
| Urea, N-(3,4-dichlorophenyl)-N,N-di methyl- | 10 mg/m³ - TWA | 10 mg/m ³ - TWAEV |

<u>Legend</u>

ACGIH - American Conference of Governmental Industrial Hygienists

Alberta - Alberta Occupational Exposure Limits

British Columbia - British Columbia Occupational Exposure Limits

Ontario - Ontario Occupational Exposure Limits

Quebec - Quebec Occupational Exposure Limits N/E - Not established

....

Engineering Measures

Personal Protective Equipment

Eye/Face Protection Skin Protection Respiratory Protection

Hygiene Measures

Ensure adequate ventilation, especially in confined areas.

Safety glasses with side-shields. Protective gloves and impervious clothing. In case of insufficient ventilation wear suitable respiratory equipment.

Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Odor **Odor Threshold** Density (lbs/gal) **Specific Gravity** pН Viscosity (cps) Solubility Water Solubility **Evaporation Rate** Vapor Pressure Vapor Density Wt. % Solids Vol. % Solids Wt. % Volatiles Vol. % Volatiles VOC Regulatory Limit (g/L) **Boiling Point (°F) Boiling Point (°C)** Freezing Point (°F) Freezing Point (°C) Flash Point (°F) Flash Point (°C) **Flash Point Method** Flammability (solid, gas) **Upper Explosion Limit** Lower Explosion Limit Autoignition Temperature (°F) Autoignition Temperature (°C) **Decomposition Temperature (°F) Decomposition Temperature (°C)** Partition Coefficient (n-octanol/water)

liquid little or no odor No information available 11.85 - 11.95 1.42 - 1.44 No information available 55 - 65 40 - 50 35 - 45 50 - 60 < 50 212 100 32 0 Not applicable Not applicable Not applicable Not applicable Not applicable Not applicable No information available No information available No information available No information available No information available

10. STABILITY AND REACTIVITY

| Reactivity | Not Applicable |
|------------------------------------|--|
| Chemical Stability | Stable under normal conditions. |
| Conditions To Avoid | Prevent from freezing. |
| Incompatible Materials | No materials to be especially mentioned. |
| Hazardous Decomposition Products | None under normal use. |
| Possibility Of Hazardous Reactions | None under normal conditions of use. |

11. TOXICOLOGICAL INFORMATION

Product Information Information on likely routes of exposure

Principal Routes of Exposure

| Acute Toxicity Product Information | No information available |
|---|--|
| Information on toxicological effects | |
| Symptoms | No information available |
| Delayed and immediate effects as well as chronic effe | cts from short and long-term exposure |
| Eye contact | May cause slight irritation |
| Skin contact | Substance may cause slight skin irritation. Prolonged or repeated contact may dry skin and cause irritation. |
| Inhalation | May cause irritation of respiratory tract. |
| Ingestion | Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. |
| Sensitization: | May cause an allergic skin reaction. |
| Neurological Effects | No information available. |
| Mutagenic Effects | No information available. |
| Reproductive Effects | No information available. |
| Developmental Effects | No information available. |
| Target Organ Effects | No information available. |
| STOT - single exposure | No information available. |
| STOT - repeated exposure | No information available. |
| Other adverse effects | No information available. |
| Aspiration Hazard | No information available. |

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

| ATEmix (oral) | 9996 mg/kg |
|-------------------------------|--------------|
| ATEmix (dermal) | 182345 mg/kg |
| ATEmix (inhalation-dust/mist) | 47 mg/L |

Component

Titanium dioxideLD50 Oral: > 10000 mg/kg (Rat)Barium sulfateLD50 Oral: > 5,000 g/kg (Rat) vendor dataKaolin, calcinedLD50 Oral: > 5000 mg/kg (Rat) vendor dataZinc oxideLD50 Oral: 5000 mg/kg (Rat)LC50 Inhalation (Dust): > 5700 mg/m³ (Rat, 4 hr.)Silica, amorphousLD50 Oral: > 5000 mg/kg (Rat)LD50 Dermal: 2,000 mg/kg (Rabbit)LC50 Inhalation (Dust): > 2 mg/LDecanedioic acid, bis(1,2,2,6,6-pentamethyl-4-piperidinyl) esterSensitization:

<u>Urea, N-(3,4-dichlorophenyl)-N,N-dimethyl-</u> LD50 Oral: 1017 mg/kg (Rat) LD50 Dermal: > 5000 mg/kg (Rat) May cause sensitization by skin contact

Chronic Toxicity

Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

| Chemical Name | IARC | NTP |
|------------------|--------------------------------|-----|
| | 2B - Possible Human Carcinogen | |
| Titanium dioxide | _ | |

• Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

Legend

IARC - International Agency for Research on Cancer NTP - National Toxicity Program OSHA - Occupational Safety & Health Administration

12. ECOLOGICAL INFORMATION

Ecotoxicity Effects

The environmental impact of this product has not been fully investigated.

Product Information

Acute Toxicity to Fish

No information available

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

Persistence / Degradability

No information available.

Bioaccumulation / Accumulation

No information available.

Mobility in Environmental Media

No information available.

<u>Ozone</u>

No information available

Component

Acute Toxicity to Fish

<u>Titanium dioxide</u> LC50: > 1000 mg/L (Fathead Minnow - 96 hr.) <u>Urea, N-(3,4-dichlorophenyl)-N,N-dimethyl-</u> LC50: 3.5 mg/L (Rainbow Trout - 96 hr.)

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method

Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

14. TRANSPORT INFORMATION

| TDG | Not regulated |
|-------------|---------------|
| ΙCAO / ΙΑΤΑ | Not regulated |
| IMDG / IMO | Not regulated |

15. REGULATORY INFORMATION

International Inventories

| TSCA: United States | Yes - All components are listed or exempt. |
|---------------------|--|
| DSL: Canada | No - Not all of the components are listed. |
| | One or more component is listed on NDSL. |

National Pollutant Release Inventory (NPRI)

NPRI Parts 1-4

This product contains the following Parts 1-4 NPRI chemicals:

| Chemical Name | CAS-No | Weight % (max) | NPRI Parts 1-4 |
|---------------|-----------|----------------|----------------|
| Zinc oxide | 1314-13-2 | 1 - 5% | Listed |

NPRI Part 5

This product contains the following NPRI Part 5 Chemicals:

None

WHMIS Regulatory Status

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.

16. OTHER INFORMATION

PPE: -

| HMIS | Health: | 1* | Flammability: | 0 | Reactivity: 0 |
|--------------------|---------|----|---------------|---|---------------|
| HMIS Legend | | | - | | - |

- 0 Minimal Hazard
- 1 Slight Hazard
- 2 Moderate Hazard
- 3 Serious Hazard
- 4 Severe Hazard
- * Chronic Hazard

X - Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada @

http://www.hc-sc.gc.ca/ewh-semt/contaminants/lead-plomb/asked_questions-questions_posees-eng.php.

| Prepared By | Product Stewardship Department Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 855-724-6802 |
|---------------------|---|
| Revision Date: | 02-May-2017 |
| Reason For Revision | Not available |

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

END OF SAFETY DATA SHEET